according to Regulation (EC) No. 1907/2006

SikaGard®-6250



Sika®

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaGard®-6250

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Surfaces protection

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex- H336: May cause drowsiness or dizziness.

posure, Category 3, Central nervous

system

ber

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Warning

according to Regulation (EC) No. 1907/2006

SikaGard®-6250



Revision Date 27.02.2017	Vei	rsion 1.0	Print Date 27.02.20
Hazard statements :	H226 H315 H319 H336 H412	Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizzir Harmful to aquatic life with long fects.	
Precautionary statements :	Prevention: P210	Keep away from heat, hot surfa open flames and other ignition samoking.	
	P261	Avoid breathing dust/ fume/ gas pours/ spray.	s/ mist/ va-
	P273	Avoid release to the environment	nt.
	P280	Wear protective gloves/ eye proprotection.	tection/ face
	Response:	•	
	P303 + P361 + P3	53 IF ON SKIN (or hair): Take ately all contaminated clothing. with water/shower.	
	P370 + P378	In case of fire: Use dry sand, dr or alcohol-resistant foam to exti	-

Hazardous components which must be listed on the label:

919-857-5 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	Classification	Concentration
CAS-No.	(REGULATION (EC)	[%]
EC-No.	No 1272/2008)	
Registration number		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics,	Flam. Liq.3; H226	>= 25 - < 50
<2% aromatics	STOT SE3; H336	
	Asp. Tox.1; H304	
919-857-5		
01-2119463258-33-XXXX [corresponding group CAS		
64742-48-9]		
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics,	Flam. Liq.3; H226	>= 10 - < 20
<2% aromatics	STOT SE3; H336	
	Asp. Tox.1; H304	
927-241-2	Aquatic Chronic3;	
01-2119471843-32-XXXX [corresponding group CAS	H412	

according to Regulation (EC) No. 1907/2006

SikaGard®-6250



Revision Date 27.02.2017 Version 1.0 Print Date 27.02.2017

64742-48-9]		
naphtha (petroleum), hydrotreated heavy	Flam. Liq.3; H226 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 5 - < 10
Sulfonic acids, petroleum, calcium salts 61789-86-4 263-093-9	Eye Irrit.2; H319	>= 1 - < 2,5
4,5-dihydro-2-heptadecyl-1H-imidazole-1-ethylamine 3010-23-9 221-133-2	Skin Corr.1B; H314 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 1 - < 2,5

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Excessive lachrymation

Erythema
Dermatitis
Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

according to Regulation (EC) No. 1907/2006

SikaGard®-6250



and symptoms.

: irritant effects Risks

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO2), Dry chemical

Unsuitable extinguishing

media

: Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not use a solid water stream as it may scatter and spread

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

according to Regulation (EC) No. 1907/2006

SikaGard®-6250

Revision Date 27.02.2017 Version 1.0



respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the

given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

: Use explosion-proof equipment. Keep away from

heat/sparks/open flames/hot surfaces. No smoking. Take pre-

cautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

according to Regulation (EC) No. 1907/2006

SikaGard®-6250





SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

DNEL

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics,

<2% aromatics

: End Use: Workers

Exposure routes: Skin contact

Value: 300 mg/m3

300 mg/kg

End Use: Workers

Exposure routes: Inhalation Value: 1500 mg/m3

End Use: Consumers

Exposure routes: Skin contact

Value: 300 mg/m3

End Use: Consumers Exposure routes: Inhalation

Value: 900 mg/m3

End Use: Consumers Exposure routes: Ingestion

Value: 300 mg/m3

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

according to Regulation (EC) No. 1907/2006

SikaGard®-6250

Revision Date 27.02.2017



long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : off-white

Odour : characteristic

Odour Threshold : No data available

Flash point : ca. 27 °C

Autoignition temperature : > 200 °C

Decomposition temperature : No data available

Lower explosion limit : 0 %(V)

Upper explosion limit : 7,0 %(V)

Flammability : No data available

Explosive properties : No data available

according to Regulation (EC) No. 1907/2006

SikaGard®-6250

Revision Date 27.02.2017 Version 1.0 Print Date 27.02.2017

Oxidizing properties : No data available

pH : not determined

Melting point/range / Freez-

ing point

: No data available

Boiling point/boiling range : ca. 130 °C

Vapour pressure : ca.10 hPa

at 20 °C

Density : ca.0,861 g/cm3

at 20 °C

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

Self-heating : , no

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

according to Regulation (EC) No. 1907/2006

SikaGard®-6250

Revision Date 27.02.2017 Version 1.0



10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.#

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3.160 mg/kg

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4.951 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

4,5-dihydro-2-heptadecyl-1H-imidazole-1-ethylamine:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.#

Serious eye damage/eye irritation

Causes serious eye irritation.#

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.# Respiratory sensitisation: Not classified based on available information.#

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.#

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.#

STOT - repeated exposure

Not classified based on available information.#

according to Regulation (EC) No. 1907/2006

SikaGard®-6250

Revision Date 27.02.2017 Version 1.0 Print Date 27.02.2017

Aspiration toxicity

Not classified based on available information.#

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics :

Toxicity to daphnia and other : EC50: > 1.000 mg/l, 48 h, Daphnia magna (Water flea)

aquatic invertebrates

4,5-dihydro-2-heptadecyl-1H-imidazole-1-ethylamine:

Toxicity to fish : LC50: 0,35 mg/l, 96 h, Fish

aquatic invertebrates

Toxicity to daphnia and other : EC50: 0,29 mg/l, 48 h, Daphnia magna (Water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

according to Regulation (EC) No. 1907/2006

SikaGard®-6250

Revision Date 27.02.2017 Version 1.0



Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

: 15 01 10* packaging containing residues of or contaminated Contaminated packaging

by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1139

14.2 Description of the goods : COATING SOLUTION

14.3 Class 14.4 Packing group : 111 Classification Code F1 Labels 3 Tunnel restriction code (D/E) 14.5 Environmentally hazard-

ous

IATA

14.1 UN number 1139

14.2 Description of the goods Coating solution

14.3 Class 14.4 Packing group Ш Labels 3 14.5 Environmentally hazard-: no

ous

IMDG

14.1 UN number 1139

14.2 Description of the goods : COATING SOLUTION

14.3 Class 14.4 Packing group : 111 Labels 3 EmS Number 1 : F-E EmS Number 2 : S-E 14.5 Marine pollutant

14.6 Special precautions for user

No data available

according to Regulation (EC) No. 1907/2006

SikaGard®-6250

Revision Date 27.02.2017



14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

: Not applicable

: Not applicable

REACH - List of substances subject to authorisation

REACH - Candidate List of Substances of Very High

(Annex XIV)

REACH Information:

All substances contained in our Products are - preregistered or registered by our upstream suppliers, and/or

- preregistered or registered by us, and/or - excluded from the regulation, and/or

- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma-

jor-accident hazards involving dangerous substances.

Quantity 1 Quantity 2

P₅c FLAMMABLE LIQUIDS 5.000 t 50.000 t

VOC-CH (VOCV) : 55,63 %

VOC-EU (solvent) : 55,63 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:

: The Chemicals (Hazard Information and Packaging for Sup-

ply) Regulations 2002

Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations

Health and Safety at Work Act 1974

Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

according to Regulation (EC) No. 1907/2006

SikaGard®-6250

Version 1.0 Revision Date 27.02.2017 Print Date 27.02.2017



SECTION 16: Other information

Full text of H-Statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Very toxic to aquatic life. H400

Very toxic to aquatic life with long lasting effects. H410 Toxic to aquatic life with long lasting effects. H411 Harmful to aquatic life with long lasting effects. H412

Full text of other abbreviations

Aquatic Acute Acute aquatic toxicity **Aquatic Chronic** Chronic aquatic toxicity Asp. Tox. Aspiration hazard Eye Irrit. Eye irritation Flammable liquids Flam. Liq. Skin Corr. Skin corrosion

STOT SE Specific target organ toxicity - single exposure

Accord européen relatif au transport international des marchandises **ADR**

> Dangereuses par Route Chemical Abstracts Service

CAS Derived no-effect level **DNEL**

Half maximal effective concentration EC50 **GHS** Globally Harmonized System

International Air Transport Association IATA

International Maritime Code for Dangerous Goods **IMDG**

Median lethal dosis (the amount of a material, given all at once, which LD50

causes the death of 50% (one half) of a group of test animals)

Median lethal concentration (concentrations of the chemical in air that LC50

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic **PNEC** Predicted no effect concentration

Regulation (EC) No 1907/2006 of the European Parliament and of the REACH

Council of 18 December 2006 concerning the Registration, Evaluation,

Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

according to Regulation (EC) No. 1907/2006

SikaGard®-6250

Revision Date 27.02.2017

Version 1.0

